

Appl. No. 10/771,406
Amendment dated: June 9, 2006
Reply to OA of: November 22, 2005

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1(currently amended). An apparatus for reducing a biological ~~waste~~ wasted sludge, said apparatus comprising:

a hydrolysis reactor for hydrolyzing the biological ~~waste~~ wasted sludge to become a hydrolyzed sludge;

a neutralization reactor for neutralizing the hydrolyzed sludge to result in production of an intermediate feed; and

a membrane bioreactor for effecting a biological decomposition of the intermediate feed;

wherein said membrane bioreactor comprises a filtration module having a permeate side and a contact side in contact with the intermediate feed, wherein liquid contained in the intermediate feed is in fluid communication with the permeate only through the filtration module; and a negative pressure source to enable the liquid to flow out of said membrane reactor via said permeate side as an effluent;

wherein said hydrolysis reactor is provided with an agitator for stirring the biological ~~waste~~ wasted sludge, and a heater for heating the biological ~~waste~~ wasted sludge;

said neutralization reactor is provided with an agitator for stirring the hydrolyzed sludge, and a heat exchanger for lowering temperature of the hydrolyzed sludge.

2(original). The apparatus as defined in claim 1, wherein said membrane bioreactor is further provided with an aeration device serving to provide the intermediate feed with an external gas.

Appl. No. 10/771,406
Amendment dated: June 9, 2006
Reply to OA of: November 22, 2005

3(original). The apparatus as defined in claim 1, wherein said aeration device comprises an aeration pipe and a blower connected with said aeration pipe whereby said blower is used to force the external gas into said membrane bioreactor via said aeration pipe.

4(original). The apparatus as defined in claim 3 further comprising a backwash pipe in communication with said blower and said permeate side of said filtration module.

5(original). The apparatus as defined in claim 1, wherein said filtration module is of a tubular or cassette construction and is made of a porous material.

6(original). The apparatus as defined in claim 5, wherein said porous material is a nonwoven material.

7(original). The apparatus as defined in claim 1, wherein said filtration module has a flux greater than $0.05 \text{ m}^3/\text{m}^2 \cdot \text{day}$.

8(original). The apparatus as defined in claim 1, wherein said intermediate feed contained in said membrane bioreactor is provided with aerobic, anoxic, or anaerobic microorganisms.

9(original). The apparatus as defined in claim 8, wherein the external gas is air or pure oxygen when the intermediate feed is provided with the aerobic microorganism; wherein the external gas is nitrogen or carbon dioxide when the intermediate feed is provided with the anoxic microorganisms; wherein the external gas is nitrogen, methane or marsh gas when the intermediate feed is provided with the anaerobic microorganisms.

Appl. No. 10/771,406
Amendment dated: June 9, 2006
Reply to OA of: November 22, 2005

10(currently amended). The apparatus as defined in claim 1, wherein said hydrolysis reactor is provided with ~~an agitator for stirring the biological wasted sludge,~~ and a pH controller for regulating pH value of the hydrolyzed sludge.

11(original). The apparatus as defined in claim 10, wherein the pH controller is used to regulate the pH value of the hydrolyzed sludge such that the pH value is greater than 9 or smaller than 3.

Claim 12(canceled).

13(previously presented). The apparatus as defined in claim 1, wherein the biological wasted sludge is heated by the heater at a temperature ranging from 50 to 100°C.

14(currently amended). The apparatus as defined in claim 11, wherein said neutralization reactor is provided with ~~an agitator for stirring the hydrolyzed sludge,~~ and a pH controller for regulating pH value of the intermediate feed.

15(original). The apparatus as defined in claim 14, wherein the pH controller is used to regulate the pH value of the intermediate feed such that the pH value of the intermediate feed is greater than 3 or smaller than 9.

Claim 16(canceled).

17(original). The apparatus as defined in claim 1, wherein the biological wasted sludge is obtained from the biological treatment unit of a wastewater treatment plant whereby the biological wasted sludge has a VSS/SS ratio ranging from 0.5 to 0.9, with VSS standing for volatile suspended solids, and with SS standing for total sludge concentration.